# 100% sealed connection



#### **Grabber®**

PlymoVent's Grabber® connects the exhaust hose to the vehicle's exhaust pipe via an inflatable rubber bladder. The Grabber® can be deflated manually by the operator, or automatically when the vehicle reaches the exit door. The unique rubber construction is perfect for applications that require a soft connection that will not damage the exhaust tailpipe.

- 100% capture of emissions
- High temperature construction, 200°C/390°F



- NOMEX® protective liner
- Will not damage vehicle
- Sizes for all applications



### **TECHNICAL DATA**

#### Grabber®, pneumatic exhaust nozzle

Prod. no.	Dimension exhaust hose	Dimension Grabber	Weight	Max pressure	Temp resistance	
GN-100-100	Ø 100 mm/4"	Ø 100 mm/4.0"	1.10 kg/2.42 lbs	1 bar/15 psi	+ 200°C/390°F	
GN-100-120	Ø 100 mm/4"	Ø 120 mm/4.8"	1.25 kg/2.75 lbs	1 bar/15 psi	+ 200°C/390°F	
GN-100-160	Ø 100 mm/4"	Ø 160 mm/6.3"	2.05 kg/4.51 lbs	1 bar/15 psi	+ 200°C/390°F	
GN-125-160	Ø 125 mm/5"	Ø 160 mm/6.3"	2.15 kg/4.73 lbs	1 bar/15 psi	+ 200°C/390°F	
GN-125-200	Ø 125 mm/5"	Ø 200 mm/8.0"	2.35 kg/5.17 lbs	1 bar/15 psi	+ 200°C/390°F	
GN-150-160	Ø 150 mm/6"	Ø 160 mm/6.3"	2.35 kg/5.17 lbs	1 bar/15 psi	+ 200°C/390°F	
GN-150-200	Ø 150 mm/6"	Ø 200 mm/8.0"	2.40 kg/5.28 lbs	1 bar/15 psi	+ 200°C/390°F	
Pressure reducing valve must be ordered separately when required.						

## Adjustable Safety Disconnect Coupling – The safest decision you can make

PlymoVent has developed a new patented adjustable Safety Disconnect Coupling. The new design allows different settings of release force suitable to all applications.








The safety disconnect coupling is to protect your investment from unexpected work place occurences, such as when a service technician forgets to remove the exhaust hose from the vehicle before moving it. The safety disconnect coupling will automatically separate to protect the vehicle and your exhaust system.

#### **TECHNICAL DATA**

#### Adjustable safety disconnect coupling

Prod. no.	Dimension	Weight
SDCA-100	100 mm/4"	0.4 kg/0.88 lbs
SDCA-125	125 mm/5"	0.5 kg/1.1 lbs
SDCA-150	150 mm/6"	0.5 kg/1.1 lbs



- Fully adjustable from 60 kg / 132 lbs to 90 kg / 200 lbs
- Soft cover will not scratch vehicle
- Easily snaps back together